



**SELECCIÓN DE ACCESORIOS FLEXL / HOW TO SELECT FLEXL ACCESSORIES**

Para seleccionar un accesorio siga los siguientes pasos:  
To select an accessory follow the next steps:

| Tamaño Rosca<br>Thread Size | Ø ext (mm) |
|-----------------------------|------------|
| PG7                         | 12,5       |
| PG9                         | 15,2       |
| PG11                        | 18,6       |
| PG13,5                      | 20,4       |
| PG16                        | 22,5       |
| PG21                        | 28,3       |
| PG29                        | 37,0       |
| PG36                        | 47,0       |
| PG42                        | 54,0       |
| PG48                        | 59,3       |



**FLEXL**

| RAL 7031 | Dn<br>mm | Dmax<br>mm | Dmin<br>mm | rmin<br>mm | r    | UNE-EN | PAG 7031 |      | PAG 9011 |      |  |
|----------|----------|------------|------------|------------|------|--------|----------|------|----------|------|--|
|          |          |            |            |            |      | 61386  | REF.     | kg/m | REF.     | kg/m |  |
|          | FLEXL 10 | 10         | 10         | 6,5        | 5    | 2432   | 2/6517   | 0,02 | 2/6526   | 0,02 |  |
|          | FLEXL 13 | 13         | 13         | 10         | 7,5  | 2432   | 2/6518   | 0,02 | 2/6527   | 0,02 |  |
|          | FLEXL 16 | 16         | 15,8       | 12         | 10   | 2432   | 2/6519   | 0,04 | 2/6528   | 0,04 |  |
|          | FLEXL 18 | 18         | 18,5       | 14,3       | 12,5 | 2432   | 2/6520   | 0,04 | 2/6529   | 0,04 |  |
|          | FLEXL 21 | 21         | 21,2       | 17         | 12,5 | 2432   | 2/6521   | 0,06 | 2/6530   | 0,06 |  |
|          | FLEXL 28 | 28         | 28,5       | 23         | 15   | 2432   | 2/6522   | 0,08 | 2/6531   | 0,08 |  |
|          | FLEXL 34 | 34         | 34,5       | 29         | 20   | 2432   | 2/6523   | 0,10 | 2/6532   | 0,10 |  |
|          | FLEXL 42 | 42         | 42,5       | 36         | 32,5 | 2432   | 2/6524   | 0,16 | 2/6533   | 0,16 |  |
|          | FLEXL 54 | 54         | 54,5       | 48         | 37,5 | 2432   | 2/6525   | 0,20 | 2/6534   | 0,20 |  |

RAL 9011

L = 1 m (3 ft)

120°C / 100°C / -40°C / -20°C

320N

RoHS

V2

HALOGEN FREE