

SP3S

	L		e	ep	Fmáx	Mmáx	Cd	GC	
	mm	inch						REF.	kg/ud
SP3S 400	400	16"	2	4	600	32	0,249	2/17308	1,07
SP3S 500	500	20"	2	4	600	32	0,312	2/17309	1,27
SP3S 600	600	24"	2	6	600	32	0,405	2/17310	1,47
SP3S 800	800	32"	2	6	600	32	0,561	2/17311	1,87

TF41 PVC (2/5627)

SP

	L		e	ep	Fmáx	Mmáx	Cd	GC		e	i304		i316	
	mm	inch						REF.	kg/ud		REF.	kg/ud	REF.	kg/ud
SP 300	300	12"	2,5	4	725	55,15	0,142	2/4734	1,11	2	2/18131	1,06	2/18465	1,06
SP 400	400	16"	2,5	4	725	55,15	0,203	2/1036	1,38	2	2/18132	1,32	2/18466	1,32
SP 500	500	20"	2,5	4	725	55,15	0,265	2/1037	1,64	-	-	-	-	-
SP 600	600	24"	2,5	6	725	55,15	0,326	2/4938	1,91	-	-	-	-	-
SP 800	800	32"	2,5	6	725	55,15	0,509	2/1038	2,44	-	-	-	-	-

TF41 PVC (2/5627)

- SCR/SRB + 2 x TEP M10x30 (2/17567-EZ)
- SHL/SP/SHR + 2/100 x DIN933 M10X30 (2/17547-i304) + 2/100 x TM41 M10 (2/17584-GC / 2/17612-i316)
- SCR/SRB + 2/100 x B2 (2/6792-GC)
- SPL/SHL/SP + 2/50 x B3 (2/8827-GC)
- SHST

SP8

	L		e	ep	Fmáx	Mmáx	Cd	GC	
	mm	inch						REF.	kg/ud
SP8 400	400	15 3/4"	2,5	8	1100	115	0,070	2/9559	2,51
SP8 500	500	19 2/3"	2,5	8	1100	115	0,088	2/9560	2,96
SP8 600	600	23 5/8"	2,5	8	1100	115	0,105	2/9561	3,4
SP8 700	700	27 5/9"	2,5	8	1100	115	0,123	2/9562	3,85
SP8 800	800	31 1/2"	2,5	8	1100	115	0,140	2/9563	4,3
SP8 1000	1000	39 3/8"	2,5	8	1100	115	0,175	2/9564	5,19
SP8 1500	1500	59"	2,5	8	1100	115	0,262	2/9565	7,43

- ISO7380 M6x25 (2/17582-EZ / 2/17601-i304) + TM41 M6 (2/17556-EZ / 2/8225-GC)
- CFBFR41 (2/10284) / ISO7380 M6x25 (2/17582-EZ / 2/17601-i304) + SSC (2/2064-EZ / 2/0363-GC) + TM41 M6 (2/17556-EZ / 2/8225-GC)
- DIN933 M10x30 (2/17547-i304) + BFE M10 (2/0864-GC) + TM41 M10 (2/17584-GC)