



TAPA CURVA VERTICAL EXTERIOR 90 GRADOS ZMX 3.1/4 ; ZMX 4

			ALU			
	A	R	P 3.1/4		P 4	
	pulgadas	pulgadas	REF.	Kg/ud	REF.	Kg/ud
	4	8	2/9438	0,28	2/13160	0,29
	6	8	2/9439	0,37	2/13161	0,39
	9	8	2/9440	0,50	2/13162	0,52
	12	8	2/9441	0,62	2/13163	0,65
	16	8	2/9442	0,80	2/13164	0,84
	18	8	2/9443	0,88	2/13165	0,92
	20	8	2/9444	0,97	2/13166	1,02
	24	8	2/9445	1,14	2/13167	1,19
	30	8	2/9446	1,40	2/13168	1,47
	36	8	2/9447	1,66	2/13169	1,74
	4	12	2/9448	0,35	2/9508	0,36
	6	12	2/9449	0,46	2/9509	0,48
	9	12	2/9450	0,62	2/9510	0,64
	12	12	2/9451	0,78	2/9511	0,81
	16	12	2/9452	1,00	2/9512	1,04
	18	12	2/9453	1,11	2/9513	1,15
	20	12	2/9454	1,21	2/9514	1,26
	24	12	2/9455	1,43	2/9515	1,48
	30	12	2/9456	1,75	2/9516	1,82
	36	12	2/9457	2,08	2/9517	2,16
	4	24	2/9458	0,57	2/9518	0,58
	6	24	2/9459	0,74	2/9519	0,76
	9	24	2/9460	1,00	2/9520	1,02
	12	24	2/9461	1,26	2/9521	1,29
	16	24	2/9462	1,61	2/9522	1,64
	18	24	2/9463	1,78	2/9523	1,82
	20	24	2/9464	1,95	2/9524	2,00
	24	24	2/9465	2,30	2/9525	2,36
	30	24	2/9466	2,82	2/9526	2,89
	36	24	2/9467	3,34	2/9527	3,42



TAPA VE'R'-90 ZMX 'A'x'P' AL



TAPA VE'R'-90 ZMX 'A'x'P' AL

Para asegurar la fijación en el exterior se usan 4 Pinzas Tapa ZMX por pieza, referencia 2/7054.