




CURVA PLANA / CURVA VERTICAL INTERIOR / CURVA VERTICAL EXTERIOR 45 GRADOS ZMX 3.1/4

				ALU					
	A	P	R	CP		VI		VE	
	pulgadas	pulgadas	pulgadas	REF	Kg/ud	REF	Kg/ud	REF	Kg/ud
 CP'R'-45 ZMX 'A'x3.1/4	4	3.1/4	8	2/7938	0,43	2/7978	0,42	2/8018	0,59
	6	3.1/4	8	2/7939	0,49	2/7979	0,44	2/8019	0,62
	9	3.1/4	8	2/7940	0,56	2/7980	0,47	2/8020	0,66
	12	3.1/4	8	2/7941	0,64	2/7981	0,50	2/8021	0,71
	16	3.1/4	8	2/7942	0,74	2/7982	0,55	2/8022	0,77
	18	3.1/4	8	2/7943	0,79	2/7983	0,57	2/8023	0,80
	20	3.1/4	8	2/7944	1,01	2/7984	0,59	2/8024	0,83
	24	3.1/4	8	2/7945	1,15	2/7985	0,64	2/8025	0,89
	30	3.1/4	8	2/7946	1,35	2/7986	0,70	2/8026	0,98
	36	3.1/4	8	2/7947	1,55	2/7987	0,77	2/8027	1,07
 VI'R'-45 ZMX 'A'x3.1/4	4	3.1/4	12	2/8918	0,51	2/12500	0,55	2/12840	1,02
	6	3.1/4	12	2/8919	0,56	2/12501	0,58	2/12841	1,07
	9	3.1/4	12	2/8920	0,64	2/12502	0,62	2/12842	1,14
	12	3.1/4	12	2/8921	0,82	2/12503	0,67	2/12843	1,22
	16	3.1/4	12	2/8922	0,95	2/12504	0,73	2/12844	1,31
	18	3.1/4	12	2/8923	1,02	2/12505	0,76	2/12845	1,35
	20	3.1/4	12	2/8924	1,09	2/12506	0,79	2/12846	1,40
	24	3.1/4	12	2/8925	1,22	2/12507	0,85	2/12847	1,49
	30	3.1/4	12	2/8926	1,42	2/12508	0,93	2/12848	1,64
	36	3.1/4	12	2/8927	1,93	2/12509	1,02	2/12849	1,77
 VE'R'-45 ZMX 'A'x3.1/4	4	3.1/4	24	2/8928	0,77	2/12510	0,68	2/12850	2,49
	6	3.1/4	24	2/8929	0,84	2/12511	0,72	2/12851	2,58
	9	3.1/4	24	2/8930	0,94	2/12512	0,77	2/12852	2,68
	12	3.1/4	24	2/8931	1,15	2/12513	0,84	2/12853	2,83
	16	3.1/4	24	2/8932	1,31	2/12514	0,91	2/12854	2,98
	18	3.1/4	24	2/8933	1,40	2/12515	0,95	2/12855	3,06
	20	3.1/4	24	2/8934	1,48	2/12516	0,99	2/12856	3,15
	24	3.1/4	24	2/8935	1,65	2/12517	1,06	2/12857	3,30
	30	3.1/4	24	2/8936	1,90	2/12518	1,16	2/12858	3,54
	36	3.1/4	24	2/8937	2,45	2/12519	1,27	2/12859	3,76



Para montar los accesorios se usan 2 juntas de unión de la altura correspondiente. Se necesitan 12 tornillos referencia 2/5392 en i304 (producto embalado en bolsas de 100)

