




TAPA CURVA VERTICAL EXTERIOR 45 GRADOS ZMX 4.1/2 ; ZMX 6

| | | | ALU | | | |
|--|----------|----------|---------|-------|---------|-------|
| | A | R | P 4.1/2 | | P 6 | |
| | pulgadas | pulgadas | REF. | Kg/ud | REF. | Kg/ud |
| | 4 | 12 | 2/9588 | 0,27 | 2/9648 | 0,29 |
| | 6 | 12 | 2/9589 | 0,34 | 2/9649 | 0,36 |
| | 9 | 12 | 2/9590 | 0,46 | 2/9650 | 0,50 |
| | 12 | 12 | 2/9591 | 0,59 | 2/9651 | 0,63 |
| | 16 | 12 | 2/9592 | 0,74 | 2/9652 | 0,80 |
| | 18 | 12 | 2/9593 | 0,83 | 2/9653 | 0,89 |
| | 20 | 12 | 2/9594 | 0,90 | 2/9654 | 0,96 |
| | 24 | 12 | 2/9596 | 1,06 | 2/9655 | 1,14 |
| | 30 | 12 | 2/9597 | 1,30 | 2/9656 | 1,40 |
| | 36 | 12 | 2/9657 | 1,54 | 2/9657 | 1,65 |
| | 4 | 24 | 2/13220 | 0,43 | 2/13240 | 0,46 |
| | 6 | 24 | 2/13221 | 0,54 | 2/13241 | 0,58 |
| | 9 | 24 | 2/13222 | 0,75 | 2/13242 | 0,80 |
| | 12 | 24 | 2/13223 | 0,95 | 2/13243 | 1,02 |
| | 16 | 24 | 2/13224 | 1,19 | 2/13244 | 1,28 |
| | 18 | 24 | 2/13225 | 1,32 | 2/13245 | 1,42 |
| | 20 | 24 | 2/13226 | 1,44 | 2/13246 | 1,55 |
| | 24 | 24 | 2/13227 | 1,71 | 2/13247 | 1,83 |
| | 30 | 24 | 2/13228 | 2,10 | 2/13248 | 2,25 |
| | 36 | 24 | 2/13229 | 2,47 | 2/13249 | 2,65 |
| | 4 | 36 | 2/13230 | 0,71 | 2/13250 | 0,76 |
| | 6 | 36 | 2/13231 | 0,87 | 2/13251 | 0,93 |
| | 9 | 36 | 2/13232 | 1,20 | 2/13252 | 1,29 |
| | 12 | 36 | 2/13233 | 1,53 | 2/13253 | 1,64 |
| | 16 | 36 | 2/13234 | 1,92 | 2/13254 | 2,06 |
| | 18 | 36 | 2/13235 | 2,12 | 2/13255 | 2,28 |
| | 20 | 36 | 2/13236 | 2,33 | 2/13256 | 2,49 |
| | 24 | 36 | 2/13237 | 2,75 | 2/13257 | 2,95 |
| | 30 | 36 | 2/13238 | 3,38 | 2/13258 | 3,62 |
| | 36 | 36 | 2/13239 | 3,97 | 2/13259 | 4,25 |



TAPA VE'R'-45 ZMX 'A x H' AL



TAPA VE'R'-45 ZMX 'A x H' AL

Para asegurar la fijación en el exterior se usan 4 Pinzas Tapa ZMX por pieza, referencia 2/7054.